

IMPROVING THROUGHPUT NETWORK USING MIMO-BEAMFORMING

**Al-Shurayfi Mushtaq Talib¹, Al-Zayadi Hayder Hudhair²,
Mykhaylo Reznikov¹, Yuriy Khlaponin³**

¹Taras Shevchenko National University of Kyiv, Ukraine

²Lviv Polytechnic National University, Ukraine

³National Aviation University, Ukraine



Mushtaq Talib AL-SHURAYFI

Date and place of birth: 1986, Baghdad, Republic of Iraq.

Education: College of Al-Rafidain University, 2008 & Kharkiv National University of Radioelectronics, 2012.

Current position & Functions: postgraduate student, since 2012.

Research interests: telecommunication systems & networks, 4G architecture.

Publications: 2 papers & 3 conference proceedings.

E-mail: mushtaq_talib2005@yahoo.com



Hayder Hudhair AL-ZAYADI

Date and place of birth: 1969, Baghdad, Republic of Iraq.

Education: College of Al-Mustansiriya University, 1998 & Kharkiv National University of Radioelectronics.

Current position & Functions: postgraduate student, since 2013.

Research interests: telecommunication systems & networks, 4G architecture.

Publications: 2 papers & 3 conference proceedings.

E-mail: hydertop@yahoo.com



Mykhaylo I. REZNIKOV, Candidate of Science (PhD)

Date and place of birth: 1956, Belgorod, Russia.

Education: Kyiv Military Institute of Control and Signals, 1978.

Current position & Functions: Head of Academic Dept of Radiotechniques & Radioelectronic Systems, since 2011.

Research interests: radiotechniques & telecommunication.

Publications: over 200 scientific publications including monographs, handbooks, papers in scientific journals, patents etc.

E-mail: mir@univ.net.ua



Yuriy I. KHLAPONIN, Candidate of Science (PhD)

Date and place of birth: 1963, Lugansk Oblast, Ukraine.

Education: Kyiv Military Institute of Control and Signals, 1985.

Current position & Functions: Associate Professor of Academic Dept of Information Security Means, since 2011.

Research interests: information security.

Publications: over 50 scientific publications including papers in scientific journals, certificates of copyright registration & conferences proceedings.

E-mail: yfcnz0408@ukr.net

Abstract. The performance of transmission Multi Input Multi Output (MIMO) beamforming for the multi subscriber in large cell with effective channel throughput has been investigated. The work procedure was based on singular value decomposition (SVD) using Single User (SU) in 3GPP Long Term Evolution (LTE). In LTE Single User – Multiple Input Multiple Output (SU-MIMO) operation mode, the data of a single user is transmitted simultaneously on several parallel data streams, using the available transmission resources, both in time and frequency dimensions. The simulation comparisons with beamforming and without beamforming have been studied for transmission in MIMO modulations. Despite the protection of information in LTE networks have their

vulnerabilities. Planned for a more comprehensive analysis of statistical data and based on them to accurately determine the feasibility of using various protective mechanisms 4G networks for different user groups.

Key words: LTE, MIMO, SU-MIMO, MU-MIMO, beamforming, throughput, Adaptive antenna.

Introduction

The main goal for wireless communication technology system is to design a radio access network with a high quality capacity and a wide coverage area [Release 10], in the last few years, a huge development had occurred to radio access for multiple antennas among the energy efficiency.

The model of multiple antennas was studied by Agilent technology [1]. The performance of adaptive antenna system for coverage and capacity channel was studied by Yasin, Liton [2], and the advantage technology and enhancement were studied by Seymour from Alcatel-Lucent [3] to understand the release 10 & 11 for LTE technology. For a MIMO beamforming, the white paper from Spirent, 2012 [4] gave the principles of the adaptive antenna.

The first LTE release 8, had covered up to 4 antennas, and the LTE-Advanced reached 8 antennas. In this paper we used SU multiple antennas to improve increase throughput transmission rate with beamforming.

1. Adaptive Antenna Basics

1.1. Antenna System Architecture

The System Architecture Evaluation (SAE) increases the data broadband efficiency and minimizes the number of node station, such as Radio Network Control (RNC), Support Node, and Gateway Serving. The change of these items is due to the SAE Gateway (GW) [1]. Figure 1 shows the architecture of LTE Radio Access Network (RAN) [1].

The evolved Node B (eNB) is a base station and the interface between it to direct the throughput data with RNC, interference S1, MME mobility management entity (MME) and serving gateway SGW is X2.




Fig. 1. LTE architecture with E-UTRAN [1]

1.2. The Adaptive Antenna System (AAS)

The adaptive antenna transmutes and receives energy between the device and the receiver. The technology of AAS is a “beamforming”. This technology considers the angle and focuses the direction with the

antenna Radiation pattern for the multiple antenna base station (BS).

Every BS will be used for multiple subscribers with higher throughput to receive and transmit at the same time over the sub-channels [2]. To increase data rate transmission, the multi BS must be used for every subscribe as shown in figure 2. The adaptive antenna focuses the coverage area, capacity and direction with higher data rate for LTE technology.




Fig.2. Multi-antenna with subscriber

2. MIMO Beamforming

Beamforming is the closed-loop transmit diversity solution adopted for LTE downlink. It is based on codebook precoding and beam forming is considered as a particular case of spatial multiplexing with only one code word and one layer. Thus, the layer mapping stage is transparent.

LTE technology went to higher levels of communication transmission. The Beamforming is incorporation of two types of different multiple antenna technology, which enable increasing data rate by spectral bandwidth. The beamforming supports the increase of coverage system, in other way Multi user MIMO (MU-MIMO) shares high data rate between multiple subscribers which increases the network efficiency as illustrated in figure 3.




Fig.3. MIMO/Beamforming in Rel-10/11 [3]

2.1. Single MIMO Beamforming System

In MIMO, the system delivers a correlation channel between the transmitter and the receiver of a width of more than a half of the signal wave length [4, 5]. Figure 4 shows coordination MIMO beamforming. The interference channel in beamforming including spatial domain cooperation, beamforming design among

cells for a predefined set of scheduled subscriber and control allocated power in each cell on frequency/ time resource of subscriber with energy flow.

In the LTE MIMO system, the increase of data rate and of capacity throughput is our target which can create beamforming with physically separating antenna elements.




Fig.4. Interference and energy flow in beamforming

The beamforming process combines the signal from each antenna element multiplied by a complex weight vector w . The output of a narrowband beamformer is obtained by summing up the antenna outputs

$$y(t) = \sum_{p=1}^{M_r} w_p^* y_i(n) = w^H y(n). \quad (1)$$

Where $y(n)$ is receive signal vector, P is receive antenna index.

Therefore, the beamformer response, or array factor, results as

$$F(\theta) = \sum_{p=1}^{M_r} w_p^* e^{[-j\frac{2\pi}{\lambda}(p-1)d \sin\theta]}. \quad (2)$$

The complex weights ($|w|$) are computed by an optimization algorithm that maximizes a certain cost function, not necessarily the direction of the signal. A beamforming that directs the beam toward the signal needs to estimate the Direction of Arrival (DoA) by applying the weights

$$w_p = |w| e^{[-j(p-1)\frac{2\pi}{\lambda}d \sin\theta]}. \quad (3)$$

There exist beamformers that optimize other cost functions, such as the maximum SNR proposed in [9] the MMSE, or the Least-Square (LS). These are referred to as optimal beamforming. Instead of trying to solve directly the equation for the optimal solution, iterative approaches have been proposed, referred to as adaptive algorithms.

These techniques are especially suited when the mobile environment is time-variable, and the weight vector (w^H) needs to be updated periodically. Considering the problem of minimizing the MSE between the received and transmitted signals, the cost function is

$$J(w) = E[|w^H y(n) - z(n)|^2]. \quad (4)$$

Where E is error estimation.

The optimal weights for MMSE are expressed as

$$w_{opt} = R_{yy}^{-1} r_{yd}. \quad (5)$$

Where R_{yy} is the correlation matrix [$M_r \times M_r$] of the received signal, and r_{yd} is the cross correlation vector between the transmitted data and the received signal.

2.2. Radio Frequency (RF) in MIMO Beamforming

The Beamforming is transmitted by the interference patterns that's mean the signal wave is transmitted from two and more than spatial separated points, and vice versa for the receiver side in the beamforming technology. The RF wave signal comes from the best directional antenna to enable the transmission by other antenna separated from the first element. The separation is half the RF carrier wavelength. Both antenna elements carry signal data to be transmitted and the signal power transmission will have the direction pattern from 0 to +/-90 degree, figure 5.




Fig.5. Radio Frequency in Beamforming [6]

2.3 Time Domain (TD) of Beamforming MIMO

Just MIMO beamforming has a spatial domain to create multiple data stream, the time domain performs duplexing, time division duplexing (TDD) it offers several advantage over frequency division duplex (FDD) system more than that is necessary.

For the single frequency band (Uplink "UL", Downlink "DL") the time slot in each directive have a seven frames structure (for the TDD fixed in resource allocation and time division "TD") as represented in [4].

Once upon a time FDD implementation beamforming is a feedback loop from the terminal to the transmitter of the DL channel.

The RF channel is a function of time, frequency and space. For the DL/UL channel, they have the same frequency dependent by space with time, and there is no different between channel states from one time to the next slot, this considered as channel estimation of DL/UL characteristics.

The array of antenna elements is weighted in order to shape the radiation diagram of the antenna pattern. In beamforming, the choice of weights depends on the algorithm used to optimize the radiation pattern which explain in section 2.1. Here, the Minimum Mean Square Error (MMSE) criterion it's used to compute the weights of the beamformer. The computation of weights in beamforming requires the knowledge of the channel coefficients. In slowly time-variant fading, the channel of a downlink Time Division Duplex (TDD) system is estimated in the uplink frame without loss of performance. On the other hand, FDD systems require a feedback channel to obtain the channel estimate at the

transmitter side, since the array response is frequency dependent.

3. System Model & Simulation

A multi-user Beamforming system is shown in figure 6. It shows the downlink Single User (SU) and Multi-User (MU) environment between base station (BS) and Subscriber (K), the transmission antenna (N) and each subscriber will connected with multi-antenna.

$$x(t) = \sum_{i=1}^K w_i s_i(t). \quad (6)$$




Fig.6. Block diagram of the multi-user beamforming system [8]

Where

M_i Is number of receiver antenna for the i th subscriber.

S_i Is transmitted data from Subscriber at time (t).

W_i Is Beamforming vector before transmission over channel.

The Beamforming is a mix between antenna technology and digital technology, the transmission $N \times 1$ for $x(n)$ broadcast over the channel, and the receiver vector $M_i \times 1$ at the i th subscriber is calculated from the following equation:

$$y(t) = H_i \sum_{k=1}^K w_k s_k(t) + z_i(t). \quad (7)$$

And the channel matrix H_i is;

$$H_i = \begin{bmatrix} h_i(1,1) & \dots & h_i(1,N) \\ \vdots & \ddots & \vdots \\ h_i(M_i,1) & \dots & h_i(M_i,N) \end{bmatrix}.$$

The complex Gaussian for H_i will be set of variables with base station independent for i and unit-variances [8]. There is an additive noise (z). The signal to noise ratio (SNR) for each user can be defined as $= 1/\sigma_i^2$ for the channel estimation in TDD or FDD where y is the standard deviation.

For a Single User Beamforming with a multi-receiver antenna, we can write the following equation by using equation (4):

$$y(t) = H_i x + Z_i, \quad (i = 1, 2, \dots, K). \quad (8)$$

Where the time is absent in equation (5). Using the singular value decomposition (SVD) for channel matrix, Equation (5) gives:

$$H_k = U_k Y_k V_k. \quad (9)$$

Where $U_k \in C^{r \times r}, V_k \in C^{n \times n}, U_k^* U_k = I, V_k^* V_k = I$.

And Z is noise, C is the Channel, I is the identity matrix and Y_k is $r \times n$ matrix.

And for Random beamforming (RBF), equation (8) and equation (9) will be:

$$y_k = U_k Y_k V_k^* s_k. \quad (10)$$

The SU-MIMO RBF will be:

$$\tilde{y}_k = U_k^H H_k V_b P_k s_k + U_k^H Z_k. \quad (11)$$

Where $k \in U, P_k$ is the power allocation matrix; V_b is a random unitary matrix generation, and when $H_k = U_k \Lambda_k V_k^H$ the formula will be:

$$\tilde{y}_k = \Lambda_k (V_k^H V_b) P_k s_k + Z_k. \quad (12)$$

Where Λ_k is a diagonal matrix with SVD, and V_b is a random unitary matrix generation.

To modify V_k to V_b , the receiver must reject the interferences in the transmitter weight vector. The transmit antenna will affect the effective RBF control channel and the supplementary precoder which are included in the SU-MIMO BF, so that equations (8, 9) can be written as

$$\tilde{y}_k = \tilde{U}_k^H (H_k W_k) V_b P_k s_k + \tilde{U}_k^H Z_k. \quad (13)$$

Where W_k is supplementary precoder matrix, which can be written

$$W_k = \begin{bmatrix} W_{k,1} & 0 \\ 0 & W_{k,2} \end{bmatrix}.$$

When the effective channel matrix \tilde{H}_k equals the $H_k W_k$ and equal the value of $\tilde{U}_k \Lambda_k V_k^H$, then the formula will be

$$\tilde{y}_k = \tilde{U}_k^H H_k W_k V_b P_k s_k + U_k^H Z_k = \tilde{\Lambda}_k (\tilde{V}_k^H V_b) P_k s_k + \tilde{Z}_k. \quad (14)$$

The transmission and receive signal can be calculate from the subscriber with beamforming MIMO. The capacities of channels can be calculate according to the power and SNR values. Interferences will be calculating more perfectly between the transmitted weight vectors.

4. Results

The of accomplishment MIMO beamforming has been analyzing by using Matlab program depending on Effective Code Rates equal to 1/3 with SU-MIMO beamforming. To calculate throughput BF or no-BF, the simulations were shown using a QPSK modulation and 16-QAM modulation.

Figures (7,8) confirmations a compression between throughput and SNR for with and without beamforming in two types of modulation. In figure 7 modulations QPSK was used, and in figure 8 modulations 16QAM was used, for two types of modulation the throughput transmission with beamforming was found to be better than without beamforming. With using QPSK, a throughput was bring into being when the SNR was zero. For 16QAM the throughput with BF was found to be higher than without BF.




Fig.7. Throughput BF vs. no BF with QPSK modulation




Fig.8. Throughput BF vs. no BF with 16QAM modulation

References

- [1] Agilent 3GPP Long Term Evolution: System Overview, Product Development, and Test Challenges/3GPP LTE standard 2009// June 2009, 5989-8139EN.
- [2] Performance Analysis of Adaptive Antenna System in LTE (4G) Using OFDM Technique/ Md. Yasin Ali, Liton Chandra Paul// International Journal of Advances in Engineering & Technology, Jan. 2013, ISSN: 2231-1963.
- [3] LTE-Advanced: Understanding 3GPP Release 10 and Beyond/ Jim Seymour, Sr. Director //4G Americas, October 22, 2012.
- [4] TD-LTE and MIMO Beamforming Principles and Test Challenges/ SPIRENT, August 2012.
- [5] Interference management in wireless networks: Practice and Theory/ Bruno Clerckx// Imperial College London, Eurecom, May 2013.

- [6] RF Beamforming Techniques Improve TD-LTE Cell-Edge Performance/ Craig Grimley// Agilent Technologies, March 2013, Available on site: www.mpdigest.com/issueArticles2013Mar/agilentDefault.asp
- [7] A Multi User Beamforming Scheme For Downlink MIMO Channels Based On Maximizing Signal-To-Leakage Ratios/ Alireza Tarighat, Mirette Sadek and Ali H. Sayed// Electrical Engineering Department University of California, April, 2012.
- [8] Effective channel control random beamforming for single user MIMO systems/ Hojae Lee, Jongrok Park, Hyukmin Son and Sanghoon Lee// Springer Science+Business Media, LLC 2012.
- [9] Adaptive arrays/ S. Applebaum// IEEE Transactions on Antennas and Propagation, vol. 24, no. 5, pp. 585-598, 1976.

UDC 004.056:621.39 (045)

Аль-Шурайфі М. Т., Аль-Заяді Х. Х., Резніков М.І., Хлапонін Ю.І. Підвищення пропускної спроможності мережі за допомогою МІМО-формування діаграми спрямованості

Анотація. Була досліджена пропускна спроможність системи з великою кількістю входів та виходів (MIMO) при формуванні діаграми спрямованості у великій мережі з ефективною пропускною здатністю каналу. Робота була заснована на сингулярному розкладанні (SVD), використовуючи Single User (SU) в 3GPP Long Term Evolution (LTE). У LTE Single User - Multiple Input Multiple Output (SU-MIMO) - режим роботи, при якому дані від одного користувача передаються одночасно кількома паралельними потоками даних, використовуючи доступні ресурси мережі як за часом так і за частотою. Для порівняння пропускної здатності проведено моделювання з формуванням діаграми спрямованості і без нього для двох типів модуляції передачі потоку. Незважаючи на наявні засоби захисту інформації в мережах LTE вони мають свої уразливості. Планується провести більш детальний аналіз статистичних даних і на їх основі точно визначити доцільність використання різних захисних механізмів мереж 4G для різних груп користувачів.

Ключові слова: LTE, MIMO, SU-MIMO, MU-MIMO, діаграма спрямованості, пропускна спроможність, адаптивна антена.

Аль-Шурайфі М. Т., Аль-Заяді Х. Х., Резніков М.І., Хлапонін Ю.І. Повышение пропускной способности сети с помощью МІМО-формирования диаграммы направленности

Аннотация. Была исследована пропускная способность системы с множеством входов и множеством выходов (MIMO) при формировании диаграммы направленности в крупной сети с эффективной пропускной способностью канала. Работа была основана на сингулярном разложении (SVD), используя Single User (SU) в 3GPP Long Term Evolution (LTE). В LTE Single User - Multiple Input Multiple Output (SU-MIMO) - режим работы, при котором данные от одного пользователя передаются одновременно несколькими параллельными потоками данных, используя доступные ресурсы сети как по времени так и по частоте. Для сравнения пропускной способности проведено моделирование с формированием диаграммы направленности и без нее для двух типов модуляции передачи потока. Несмотря на имеющиеся средства защиты информации в сетях LTE они имеют свои уязвимости. Планируется провести более детальный анализ статистических данных и на их основе точно определить целесообразность использования различных защитных механизмов сетей 4G для различных групп пользователей.

Ключевые слова: LTE, MIMO, SU-MIMO, MU-MIMO, диаграмма направленности, пропускная способность, адаптивная антенна.

Отримано 17 лютого 2014 року, затверджено редколегією 10 березня 2014 року